

Maximum Run Distance

PER POWER FEED

Single or Dual Circuit; ADEZ* or GEB10 ballast options; with or without emergency options.

		Lamp Type	120V	277V	347V
Lamps in Cross Section	1	54T5HO	56'	124'	160'
	2	54T5HO	28'	64'	80'
	3	54T5HO	16'	40'	52'
	4	54T5HO	12'	32'	40'
	1	28T5 and 32 (T8)	104'	240'	292'
	2	28T5 and 32 (T8)	52'	120'	148'
	3	28T5 and 32 (T8)	36'	80'	96'
	4	28T5 and 32 (T8)	24'	60'	72'

*ADEZ not available with dual circuits

Single Circuit; ADZT ballast options with dimming; with or without emergency options


		Lamp Type	120V	277V	347V
Lamps in Cross Section	1	54T5HO	40'	96'	N/A
	2	54T5HO	20'	48'	N/A
	3	54T5HO	12'	36'	N/A
	4	54T5HO	8'	24'	N/A
	1	28T5 and 32 (T8)	72'	172'	N/A
	2	28T5 and 32 (T8)	36'	84'	N/A
	3	28T5 and 32 (T8)	24'	56'	N/A
	4	28T5 and 32 (T8)	16'	40'	N/A

Standard Maximum Section Length Layout

- For 16' runs R12 is not available.
- For longer runs, 4' sections (U4) will not be used on any R12 breakouts.

Example for 28' R12 run:

CORRECT



INCORRECT

